

# L85SA-R-DC-10

## 10cd red aeronautical obstruction light

A new generation of LED low intensity aeronautical obstruction lights to meet the demanding requirements of offshore environmental conditions. The design is based on low power long life LED technology and use of stainless steel. These fittings meet the regulatory requirements for ICAO, CAP437/168, the Mining regulations of the Netherlands and IMO.



### KEY FEATURES

- Reliable low intensity aeronautical obstruction light
- Low cost of ownership
- Low power consumption
- Serviceable unit, parts are interchangeable
- Compact design
- Impact resistant dome and stainless steel body
- Spacious, easy to open cable connection compartment

### PERFORMANCE CHARACTERISTICS

- Steady burning; red
- Intensity: 10cd minimum
- Horizontal coverage: 360°
- Vertical beam profile: Visible from any point above the horizon
- Colour chromaticity within the boundaries as specified by ICAO
- Light source: LED  
(100,000 hours average life)

### STANDARDS/CERTIFICATION

- Certified to ICAO Annex 14, volume I; Aerodrome design and operations, 6th Edition, 2013, chapter 6.3.2 – Type A low intensity obstacle light
- Certified to IMO standard MODU code; 2009 (Edition 2010), chapter 13.5.24
- Certified to CAA-UK CAP 437; Offshore helicopter landing areas – Guidance on standards, 7th edition, chapter 4, paragraph 4.3
- Complies with CAA-UK CAP 168; July 2010, chapter 4, paragraph 12.8.1a, 12.10.2, 12.11.3 and table 6A.1.11 – Low intensity aeronautical obstruction light – Group A
- Certified to German “General Administrative Regulation for the marking and lighting of obstacles to air avigation” Low Intensity Type A / Hindernisfeuer
- Certified to Mining regulations of the Netherlands; 2002, article 5.5

### ELECTRICAL CHARACTERISTICS

- Operating voltage: 20-30Vdc
- Power consumption: 2W
- Connection details:  
M4; two M25x1.5 cable entries
- Earth connection: internal M4 and external M6

### PHYSICAL CHARACTERISTICS

- Dimensions (L x W x H):  
161 x 161 x 111mm
- Weight: 3.6kg
- Design degree of protection: IP66
- Operating temperature range:  
-40°C to +60°C



# L85SA-R-DC-10

10cd red aeronautical obstruction light

