

L85SA-R-DC-200

200cd red aeronautical obstruction light

A new generation of LED low intensity aeronautical obstruction lights to meet the demanding requirements of offshore environmental conditions. The design is based on low power long life LED technology and use of stainless steel. These fittings meet the regulatory requirements for CAP437/168.



KEY FEATURES

- Reliable low intensity aeronautical obstruction light
- Low cost of ownership
- Low power consumption
- Serviceable unit, parts are interchangeable
- Compact design
- Impact resistant dome and stainless steel 316 body
- Spacious, easy to open cable connection compartment

STANDARDS/CERTIFICATION

- Complies with CAA-UK CAP 437; Offshore helicopter landing areas – Guidance on standards, 7TH edition Feb 2013, chapter 4, paragraph 4.4

PERFORMANCE CHARACTERISTICS

- Steady burning; red
- Intensity: 200cd minimum (between 5° – 8°) and 50cd minimum (between 0° – 15°)
- Horizontal coverage: 360°
- Vertical beam profile: as per CAP168 Chapter 4 and Appendix 6, Table 6A.1, Group B
- Colour chromaticity within the boundaries as specified by ICAO
- Light source: LED (100,000 hours average life)

ELECTRICAL CHARACTERISTICS

- Operating voltage: 20-30Vdc
- Power consumption: 7,5W
- Connection details: M4; two M25x1.5 cable entries
- Earth connection: internal M4 and external M6

PHYSICAL CHARACTERISTICS

- Dimensions (L x W x H): 161 x 161 x 111mm
- Weight: 3.6kg
- Design degree of protection: IP66
- Operating temperature range: -40°C to +55°C



L85SA-R-DC-200

200cd red aeronautical obstruction light

