

FH800SA-3

Explosion proof foghorn

Foghorn, designed to provide 2 nautical miles omni-directional coverage. For man-made offshore structures and in line with IALA regulatory requirements. Can be supplied as a combined main/secondary (2 1/2 NM) foghorn together with duplicated controls in the Navaid Central Control Panel (NCCP).



KEY FEATURES

- Reliable marine foghorn, low cost of ownership
- Operating voltage and code control provided from Navaid Central Control Panel (NCCP)
- Monitoring system integrated in Navaid Central Control Panel (NCCP)
- Offshore coated seawater resistant light alloy body
- Can be supplied as a main/secondary (2 1/2 Nm) foghorn together with duplicated controls in the Navaid Central

STANDARDS/CERTIFICATION

- Complies with IALA regulation; O-139 The marking of man-made offshore structures – Dec. 2013; chapter 2, paragraph 2.1.2.2 – Fogsignal
- Complies with UK Department of Energy and Climate Change; Standard marking schedule for offshore installations – April 2011; chapter 4 – secondary fog signal
- Complies with Mining regulations of the Netherlands – Dec. 2002, Article 5.2 – Fogsignal
- Complies with US Coast Guard; 33 C.F.R. Part 67 – Aids to navigation on artificial islands and fixed structures

PERFORMANCE CHARACTERISTICS

- Morse code 'U' every 30 s from Navaid Central Control Panel (NCCP)
- Alternative codes available; USCG 2 s blast every 20 s (2 s sound, 18 s silence)
- Usual range main foghorn: 2.0 NM (134 dB(A) at 1 m)
- Horizontal sound output: 360°

ELECTRICAL CHARACTERISTICS

- Operating voltage: 190 Vac; 860 Hz from Navaid Central Control Panel (NCCP)
- Power consumption: 100 W peak (Classic NCCP); 80 W peak max (Digital modular NCCP)
- Connection details: max. 4 mm²; one M25x1.5 cable gland entry
- Earth connection: internal 4 mm² and external M6

PHYSICAL CHARACTERISTICS

- Dimensions (L x W x H): 678 x 464 x 1900 mm
- Weight: 175 kg
- Design degree of protection: IP66
- Operating temperature range: -55 °C to +55 °C

SYSTEM DESIGN, CONTROL AND MONITORING

- Control and monitoring via separate control panel (see separate product information sheet)

FH800SA-3

Explosion proof foghorn

