

L410SA-W-15N

Explosion proof LED main marine light (15 NM)

Main marine light providing 15 nautical mile white omni-directional coverage, for offshore structures. The design, with long life LEDs, makes the product ideal for the environmental conditions, easy installation and long maintenance intervals.



KEY FEATURES

- Reliable marine navigation light, low cost of ownership and low power consumption
- 'U'-coded high voltage AC power supply from Navais Central Control Panel for low cable costs and failure free synchronisation
- Offshore coated, lightweight, corrosion free, seawater, UV and humidity resistant light alloy base
- Stainless steel mounting facilities to prevent corrosion problems
- Integrated connection box
- Very low power consumption due to efficient optical design
- Anti bird spikes (to prevent bird fouling)

STANDARDS/CERTIFICATION

- Complies with UK Department of Energy and Climate Change; Standard marking schedule for offshore installations – April 2011, chapter 3.1 (c) – Main lights

PERFORMANCE CHARACTERISTICS

- Flashing white light, Morse code 'U' every 15 seconds by NCCP
- Effective intensity: 15 NM light: 12,000cd minimum (equals 15 NM at ATF=0.74)
- Horizontal beam coverage: 360°
- Vertical beam profile: 2.5° FWTM minimum

ELECTRICAL CHARACTERISTICS

- Operating voltage ('U'-Coded from the NCCP): 15 NM light: 230Vac; 50-60Hz
- Power consumption: 15 NM light: 125 W peak; 21 W average
- Connection details: 15 NM light: max. 4 mm²; M25 cable gland entry
- Earth connection: internal max. 4 mm² and external M5

PHYSICAL CHARACTERISTICS

- Dimensions (L x W x H): 447x416x896
- Weight: 40 kg
- Degree of protection: IP66
- Operating temperature range: -40°C to +50°C

SYSTEM DESIGN, CONTROL AND MONITORING

- Control and monitoring via separate control panel (see separate product information sheet)

L410SA-W-15N

Explosion proof LED main marine light (15 NM)

