

OSP200EX-xxx

Explosion proof solar power module

The OSP200EX is Orga's Zone 1 explosion proof solar power module designed to be used in the Orga solar power systems.



KEY FEATURES

- Double glass technology
- Suitable for Zone 1 and Zone 2 areas with gas explosion hazard
- Excellent mechanical properties and reliability

STANDARDS/CERTIFICATION

- Cenelec EN 60079-0, EN 60079-7 and EN 60079-18
- KIWA 20ATEX0001 X; ATEX II 2 G Ex eb mb IIC T5 Gb
- IEC 60079-0, IEC 60079-7 and IEC 60079-18
- IECEx KIWA 20.0001X; Ex eb mb IIC T5 Gb

PERFORMANCE CHARACTERISTICS

- See table

ELECTRICAL CHARACTERISTICS

- Connection details: M4; two M25x1.5 Ex e cables glands with gland plugs
- Bypass diodes included
- System voltages of 24 volt and higher can be obtained by connecting modules in series
- Designed for use in positively grounded solar systems. For systems with negatively ground load, consumers power supply to load is via an isolated DC/DC converter provided as a part of the Orga solar power supply system

PHYSICAL CHARACTERISTICS

- Dimensions (L x W x H): 1271 x 554 x 74 mm
- Design degree of protection: IP66
- Weight: 25 kg
- Operating temperature range: -25 °C to +50 °C
- Solar cells are encapsulated between high transmission tempered glass
- Anodised aluminium frame for easy mounting

OPTIONAL ACCESSORIES

- Optional non-metallic cover to protect the Solar panel during installation, commissioning and drilling against dirt and falling objects
 - MUD resistant
 - Impact resistant
 - UV stable
 - Lightweight: 3 kg
 - Stackable



OSP200EX-xxx

Explosion proof solar power module

Typical data at Standard Test Conditions (STC): 1000 W/m² irradiance level, AM 1.5 spectrum and 25°C cell temperature

	Maximum power point (mpp) (+/- 5%)	Output voltage at mpp	Current at mpp	Short circuit current	Open circuit voltage
OSP200EX-108	108 W	20,9 Vdc	5,2 A	5,5 A	24,8 Vdc
OSP200EX-120	120 W	22,0 Vdc	5,4 A	5,8 A	25,9 Vdc

